





## CLAMPS

Mikalor Clamps.....	232-234
Powerflex: Single Bolt Clamps.....	235
Powerflex: Double Bolt Clamps.....	236-237
ASL High Pressure Safety Clamp.....	238
Double Bolt Heavy Duty Clamps.....	239
Hose Clamps.....	240
DIN 2817 Clamps in Aluminium.....	241
TRI Clamp Unions.....	242
Notes.....	243



## SUPER CLAMPS (W1)

### FEATURES & BENEFITS

- Heavy Duty
- High Tensile Strength
- Easy Assembly
- Reliable, Durable & Effective
- Bevelled Edges protect Hoses

### APPLICATIONS

- Agricultural Market Segments
- Waste Water Extraction
- Mining and Quarrying Equipment

### TECHNICAL SPECIFICATION

- 33 Sizes 17-19mm to 240-252mm
- Carbon Steel, Zinc Plated & White Zinc Plated
- 8.8 Grade Steel nut and T-Bolt
- Pressure: 3 to 48 Bar
- Torque 4.5 to 50 Nm

### CARBON STEEL, WHITE ZINC PLATED

Product Code	Size
SC17-19-GOLD	17mm-19mm
SC20-22-GOLD	20mm-22mm
SC23-25-GOLD	23mm-25mm
SC26-28-GOLD	26mm-28mm
SC29-31-GOLD	29mm-31mm
SC32-35-GOLD	32mm-35mm
SC36-39-GOLD	36mm-39mm
SC40-43-GOLD	40mm-43mm
SC44-47-GOLD	44mm-47mm
SC48-51-GOLD	48mm-51mm
SC52-55-GOLD	52mm-55mm
SC56-59-GOLD	56mm-59mm
SC60-63-GOLD	60mm-63mm
SC64-67-GOLD	64mm-67mm
SC68-73-GOLD	68mm-73mm
SC74-79-GOLD	74mm-79mm
SC80-85-GOLD	80mm-85mm
SC86-91-GOLD	86mm-91mm
SC92-97-GOLD	92mm-97mm
SC98-103-GOLD	98mm-103mm
SC104-112-GOLD	104mm-112mm
SC113-121-GOLD	113mm-121mm
SC122-130-GOLD	122mm-130mm
SC131-139-GOLD	131mm-139mm
SC140-148-GOLD	140mm-148mm
SC149-161-GOLD	149mm-161mm
SC162-174-GOLD	162mm-174mm
SC175-187-GOLD	175mm-187mm
SC188-200-GOLD	188mm-200mm
SC201-213-GOLD	201mm-213mm
SC214-226-GOLD	214mm-226mm
SC227-239-GOLD	227mm-239mm
SC240-252-GOLD	240mm-252mm



## SUPRA FERRITIC CLAMPS (W2)

### FEATURES & BENEFITS

- Heavy Duty
- High Tensile Strength
- Easy Assembly
- Reliable
- Durable & Effective
- Bevelled Edges protect Hoses

### APPLICATIONS

- Agricultural Market Segments
- Waste Water Extraction
- Mining and Quarrying Equipment
- Low Pressure Connections

### TECHNICAL SPECIFICATION

- 36 Sizes 17-19mm to 240-252mm
- 304 Stainless Steel
- Strengthened Bolt: Zinc Plated Mild Steel
- Pressure: 3 to 48 Bar
- Torque 4.5 to 50 Nm
- Complies fully with the RoHs Directive EU 20032/95/EC (1 July)

### 304 STAINLESS STEEL

Product Code	Size
SC17-19-SUF	17mm-19mm
SC19-21-SUF	19mm-21mm
SC21-23-SUF	21mm-23mm
SC23-25-SUF	23mm-25mm
SC25-27-SUF	25mm-27mm
SC27-29-SUF	27mm-29mm
SC29-31-SUF	29mm-31mm
SC31-34-SUF	31mm-34mm
SC34-37-SUF	34mm-37mm
SC37-40-SUF	37mm-40mm
SC40-43-SUF	40mm-43mm
SC43-47-SUF	43mm-47mm
SC47-51-SUF	47mm-51mm
SC51-55-SUF	51mm-55mm
SC55-59-SUF	55mm-59mm
SC59-63-SUF	59mm-63mm
SC63-68-SUF	63mm-68mm
SC68-73-SUF	68mm-73mm
SC73-79-SUF	73mm-79mm
SC79-85-SUF	79mm-85mm
SC85-91-SUF	85mm-91mm
SC91-97-SUF	91mm-97mm
SC97-104-SUF	97mm-104mm
SC104-112-SUF	104mm-112mm
SC112-121-SUF	112mm-121mm
SC121-130-SUF	121mm-130mm
SC130-140-SUF	130mm-140mm
SC140-150-SUF	140mm-150mm
SC150-162-SUF	150mm-162mm
SC162-174-SUF	162mm-174mm
SC174-187-SUF	174mm-187mm
SC187-200-SUF	187mm-200mm
SC200-213-SUF	200mm-213mm
SC213-226-SUF	213mm-226mm
SC226-239-SUF	226mm-239mm
SC239-252-SUF	239mm-252mm



## SUPRA CLAMPS (W4)

### FEATURES & BENEFITS

- Heavy Duty
- High Corrosion Resistance
- Easy to fit without disconnecting the Hose
- Swivelling Bridge
- Bevelled Edges protect Hoses

### APPLICATIONS

- Low Pressure Marine
- Food Processing
- Industrial Applications where AISI 302 Stainless Steel is specified

### TECHNICAL SPECIFICATION

- 36 Sizes 17-19mm to 240-252mm
- Full 304 Stainless Steel
- DIN 1.4301 Standard
- Pressure: 3 to 40 Bar
- Torque 10 to 50 Nm
- Complies fully with the RoHs Directive EU 20032/95/EC (1 July)

### COMPLETE AISI 302 STAINLESS STEEL

Product Code	Size
SC17-19-SS	17mm-19mm
SC19-21-SS	19mm-21mm
SC21-23-SS	21mm-23mm
SC23-25-SS	23mm-25mm
SC25-27-SS	25mm-27mm
SC27-29-SS	27mm-29mm
SC29-31-SS	29mm-31mm
SC31-34-SS	31mm-34mm
SC34-37-SS	34mm-37mm
SC37-40-SS	37mm-40mm
SC40-43-SS	40mm-43mm
SC43-47-SS	43mm-47mm
SC47-51-SS	47mm-51mm
SC51-55-SS	51mm-55mm
SC55-59-SS	55mm-59mm
SC59-63-SS	59mm-63mm
SC63-68-SS	63mm-68mm
SC68-73-SS	68mm-73mm
SC73-79-SS	73mm-79mm
SC79-85-SS	79mm-85mm
SC85-91-SS	85mm-91mm
SC91-97-SS	91mm-97mm
SC97-104-SS	97mm-104mm
SC104-112-SS	104mm-112mm
SC112-121-SS	112mm-121mm
SC121-130-SS	121mm-130mm
SC130-140-SS	130mm-140mm
SC140-150-SS	140mm-150mm
SC150-162-SS	150mm-162mm
SC162-174-SS	162mm-174mm
SC174-187-SS	174mm-187mm
SC187-200-SS	187mm-200mm
SC200-213-SS	200mm-213mm
SC213-226-SS	213mm-226mm
SC226-239-SS	226mm-239mm
SC239-252-SS	239mm-252mm

## SUMMARY

**These Mikalor clamps** offers a cost effective easy to use and safe method of clamping fittings in your hose assembly.

It is the market leader in Europe because of its quality and reliability and Action-Sealtite offer the largest selections at the most competitive prices.



# POWERFLEX: SINGLE BOLT CLAMPS



## SINGLE BOLT CLAMPS

### FEATURES & BENEFITS

- Offers a Large size range for a single bolt
- 316 Stainless Steel is acid and sea water resistant

### APPLICATIONS

- Hose Assemblies
- Manufacturing
- Agriculture
- Hydraulics
- Chemical
- Food
- Sea Water applications

### TECHNICAL SPECIFICATION

- Sizes 20-22mm to 227-239mm
- 316 Stainless Steel

### SINGLE BOLT SUPER CLAMP W5 STAINLESS STEEL 316

Product Code	Size	Material
SCS20-22-PF	20mm-22mm	316 Stainless Steel
SCS23-25-PF	23mm-25mm	316 Stainless Steel
SCS29-31-PF	29mm-31mm	316 Stainless Steel
SCS32-35-PF	32mm-35mm	316 Stainless Steel
SCS36-39-PF	36mm-39mm	316 Stainless Steel
SCS40-43-PF	40mm-43mm	316 Stainless Steel
SCS44-47-PF	44mm-47mm	316 Stainless Steel
SCS48-51-PF	48mm-51mm	316 Stainless Steel
SCS52-55-PF	52mm-55mm	316 Stainless Steel
SCS56-59-PF	56mm-59mm	316 Stainless Steel
SCS60-63-PF	60mm-63mm	316 Stainless Steel
SCS64-67-PF	64mm-67mm	316 Stainless Steel
SCS74-79-PF	74mm-79mm	316 Stainless Steel
SCS80-85-PF	80mm-85mm	316 Stainless Steel
SCS86-91-PF	86mm-91mm	316 Stainless Steel
SCS92-97-PF	92mm-97mm	316 Stainless Steel
SCS104-112-PF	104mm-112mm	316 Stainless Steel
SCS113-121-PF	113mm-121mm	316 Stainless Steel
SCS131-139-PF	131mm-139mm	316 Stainless Steel
SCS140-148-PF	140mm-148mm	316 Stainless Steel
SCS149-161-PF	149mm-161mm	316 Stainless Steel
SCS175-187-PF	175mm-187mm	316 Stainless Steel
SCS214-226-PF	214mm-226mm	316 Stainless Steel
SCS227-239-PF	227mm-239mm	316 Stainless Steel

## SUMMARY

At Action Sealtite we can supply industry leading quality hose clamps from Powerflex. Powerflex hose clamps are used in various applications where only the highest quality product will suffice.

The 316 Stainless Steel has the advantages of being a superior Stainless Steel Clamp to those usually made from 304 grade Stainless Steel.

# POWERFLEX/ASL: DOUBLE BOLT CLAMPS



## FEATURES & BENEFITS

- Will not split or crack when subject to a high torque pressure
- 316 Stainless Steel is acid and sea water resistant
- Greater size range compared to single bolts clamps

## APPLICATIONS

- High Pressure Air Lines
- Manufacturing
- Agriculture
- Hydraulics
- General Engineering
- Chemical
- Food
- Sea Water applications

## TECHNICAL SPECIFICATION

- Sizes 35-40mm to 360-375mm
- Plated steel & 316 Stainless Steel
- Band Widths: 20mm & 25mm (Powerflex), 24mm (ASL)
- Designed to give a solid clamp connection on the hose

## PLATED STEEL/316 STAINLESS STEEL DOUBLE BOLT CLAMP, BAND WIDTH: 20MM

Product Code	Size mm	Band Width	Material
DBC20-1-2-050-PS	44mm-50mm	20mm	Plated Steel
DBC20-1-2-060-PS	54mm-60mm	20mm	Plated Steel
DBC20-1-2-065-PS	59mm-65mm	20mm	Plated Steel
DBC20-1-2-075-PS	69mm-75mm	20mm	Plated Steel
DBC20-1-2-080-PS	70mm-80mm	20mm	Plated Steel
DBC20-1-2-085-PS	79mm-85mm	20mm	Plated Steel
DBC20-1-2-040-SS	35mm-40mm	20mm	316 Stainless Steel
DBC20-1-2-080-SS	74mm-80mm	20mm	316 Stainless Steel

## PLATED STEEL/316 STAINLESS STEEL DOUBLE BOLT CLAMP, BAND WIDTH: 24MM

Product Code	Size mm	Band Width	Material
DBC24-6575-W1	65mm-75mm	24mm	Plated Steel
DBC24-8090-W1	80mm-90mm	24mm	Plated Steel
DBC24-95105-W1	95mm-105mm	24mm	Plated Steel
DBC24-100110-W1	100mm-110mm	24mm	Plated Steel
DBC24-105115-W1	105mm-115mm	24mm	Plated Steel
DBC24-110120-W1	110mm-120mm	24mm	Plated Steel
DBC24-120130-W1	120mm-130mm	24mm	Plated Steel
DBC24-125135-W1	125mm-135mm	24mm	Plated Steel
DBC24-130140-W1	130mm-140mm	24mm	Plated Steel
DBC24-150160-W1	150mm-160mm	24mm	Plated Steel
DBC24-160170-W1	160mm-170mm	24mm	Plated Steel
DBC24-200210-W1	200mm-210mm	24mm	Plated Steel
DBC24-210220-W1	210mm-220mm	24mm	Plated Steel
DBC24-260275-W1	260mm-275mm	24mm	Plated Steel
DBC24-270285-W1	270mm-285mm	24mm	Plated Steel
DBC24-360375-W1	360mm-375mm	24mm	Plated Steel
DBC24-7585-W4	75mm-85mm	24mm	316 Stainless Steel
DBC24-200210-W4	200mm-210mm	24mm	316 Stainless Steel
DBC24-310325-W4	310mm-325mm	24mm	316 Stainless Steel

# POWERFLEX: DOUBLE BOLT CLAMPS

## PLATED STEEL DOUBLE BOLT CLAMP, BAND WIDTH: 25MM

Product Code	Size mm	Band Width	Material
DBC25-1-2-080-PS	70mm-80mm	25mm	Plated Steel
DBC25-1-2-085-PS	75mm-85mm	25mm	Plated Steel
DBC25-1-2-090-PS	80mm-90mm	25mm	Plated Steel
DBC25-1-2-095-PS	85mm-95mm	25mm	Plated Steel
DBC25-1-2-110-PS	100mm-110mm	25mm	Plated Steel
DBC25-1-2-115-PS	105mm-115mm	25mm	Plated Steel
DBC25-1-2-120-PS	110mm-120mm	25mm	Plated Steel
DBC25-1-2-125-PS	115mm-125mm	25mm	Plated Steel
DBC25-1-2-135-PS	125mm-135mm	25mm	Plated Steel
DBC25-1-2-140-PS	130mm-140mm	25mm	Plated Steel
DBC25-1-2-145-PS	135mm-145mm	25mm	Plated Steel
DBC25-1-2-150-PS	140mm-150mm	25mm	Plated Steel
DBC25-1-2-155-PS	145mm-155mm	25mm	Plated Steel
DBC25-1-2-160-PS	150mm-165mm	25mm	Plated Steel
DBC25-1-2-165-PS	155mm-170mm	25mm	Plated Steel
DBC25-1-2-170-PS	160mm-175mm	25mm	Plated Steel
DBC25-1-2-175-PS	165mm-180mm	25mm	Plated Steel
DBC25-1-2-220-PS	210mm-225mm	25mm	Plated Steel
DBC25-1-2-230-PS	220mm-235mm	25mm	Plated Steel
DBC25-1-2-240-PS	240mm-255mm	25mm	Plated Steel
DBC25-1-2-250-PS	250mm-255mm	25mm	Plated Steel
DBC25-1-2-260-PS	250mm-265mm	25mm	Plated Steel
DBC25-1-2-270-PS	260mm-275mm	25mm	Plated Steel
DBC25-1-2-280-PS	270mm-285mm	25mm	Plated Steel
DBC25-1-2-290-PS	280mm-295mm	25mm	Plated Steel
DBC25-1-2-300-PS	290mm-305mm	25mm	Plated Steel
DBC25-1-2-310-PS	300mm-315mm	25mm	Plated Steel
DBC25-1-2-320-PS	310mm-325mm	25mm	Plated Steel
DBC25-1-2-330-PS	320mm-35mm	25mm	Plated Steel
DBC25-1-2-340-PS	330mm-345mm	25mm	Plated Steel
DBC25-1-2-350-PS	340mm-355mm	25mm	Plated Steel
DBC25-1-2-360-PS	350mm-365mm	25mm	Plated Steel
DBC25-1-2-370-PS	360mm-375mm	25mm	Plated Steel



## 316 STAINLESS STEEL DOUBLE BOLT CLAMP, BAND WIDTH: 25MM

Product Code	Size mm	Band Width	Material
DBC25-1-2-070-SS	60mm-70mm	25mm	316 Stainless Steel
DBC25-1-2-080-SS	70mm-80mm	25mm	316 Stainless Steel
DBC25-1-2-085-SS	75mm-85mm	25mm	316 Stainless Steel
DBC25-1-2-090-SS	80mm-90mm	25mm	316 Stainless Steel
DBC25-1-2-105-SS	95mm-105mm	25mm	316 Stainless Steel
DBC25-1-2-125-SS	115mm-125mm	25mm	316 Stainless Steel
DBC25-1-2-130-SS	120mm-130mm	25mm	316 Stainless Steel
DBC25-1-2-145-SS	135mm-145mm	25mm	316 Stainless Steel
DBC25-1-2-175-SS	165mm-180mm	25mm	316 Stainless Steel
DBC25-1-2-180-SS	170mm-185mm	25mm	316 Stainless Steel
DBC25-1-2-190-SS	180mm-195mm	25mm	316 Stainless Steel
DBC25-1-2-210-SS	200mm-215mm	25mm	316 Stainless Steel
DBC25-1-2-220-SS	210mm-225mm	25mm	316 Stainless Steel
DBC25-1-2-230-SS	220mm-235mm	25mm	316 Stainless Steel
DBC25-1-2-260-SS	250mm-265mm	25mm	316 Stainless Steel
DBC25-1-2-270-SS	260mm-275mm	25mm	316 Stainless Steel
DBC25-1-2-280-SS	270mm-285mm	25mm	316 Stainless Steel
DBC25-1-2-320-SS	310mm-325mm	25mm	316 Stainless Steel
DBC25-1-2-330-SS	320mm-335mm	25mm	316 Stainless Steel
DBC25-1-2-340-SS	330mm-345mm	25mm	316 Stainless Steel

## SUMMARY

The **POWERFLEX/ASL Double Bolt Clamp** is very suitable to applications where higher pressures and greater strengths are required. The Double Bolt Clamp system provides greater size range and wider band widths.

The Double Bolt Clamps are available in two materials: Galvanized known as Plated Steel and 316 Stainless Steel.



# ASL HIGH PRESSURE SAFETY CLAMP



## FEATURES & BENEFITS

- Reusable
- Robust
- ASL Branded
- 'Bolt-shelf' for one handed spanner tightening
- Larger sizes available upon request

## APPLICATIONS

- High Pressure Hose Assemblies
- Steam
- Compressed Air

## TECHNICAL SPECIFICATION

- Sizes 1/2" to 1" Inner Diameter
- Plated Steel #35
- Sizes to 3/4" have 2 Bolts
- 1" sizes have 4 Bolts
- Interlocking – Extended Finger engages behind security collar
- Ribbed

## SUMMARY

These clamps are reusable and of robust construction. Widely used in Oil Refineries, Chemical Plants and other factories using Steam as an essential service. As Steam is a dangerous medium, please take care when specifying and fitting the correct size clamp.

## HIGH PRESSURE CLAMPS

Product Code	Hose LD ins	mm	Hose ID (mm) min	min	Material
HPC01	1/2	13	21	25	Plated Steel #35
HPC02	1/2	13	25	29	Plated Steel #35
HPC03	1/2	13	29	31	Plated Steel #35
HPC04	3/4	19	31	34	Plated Steel #35
HPC04	3/4	19	30	33	Plated Steel #35
HPC05	3/4	19	34	37	Plated Steel #35
HPC06	3/4	19	37	40	Plated Steel #35
HPC08	1	25	39	42	Plated Steel #35

**Note:** Other sizes available upon request.

# DOUBLE BOLT HEAVY DUTY CLAMPS

**LÜDECKE**

Since 1930. The perfect connection.

## FEATURES & BENEFITS

- Will not split or crack when subjected to high torque pressures
- Reliable
- Full Circumference hose grip
- 'Bolt-shelf' for one handed spanner tightening
- Fitted with spacers and have 'gripping' power
- The SK clamp has an extended finger which engages behind the security collar

## TECHNICAL SPECIFICATION

- Sizes 22-29mm to 227-250mm
- Materials: Malleable Iron, Zinc Plated & Yellow Chromate
- Free from Chrome VI
- Designed to give a solid clamp connection on hoses



## APPLICATIONS

- Low to Medium pressure air lines
- Compressor Hoses
- Suction and Delivery Hoses

## SUMMARY

**Ludecke Double Bolt Heavy-Duty clamps** for use in high pressure applications. The Double Bolt Clamp is fitted with spacers and has 'gripping' power in excess of most other brand clamps. These protect the hose being pinched, ensure full circumference hose grip and prevent the clamp from damaging the hose.

The clamp is heavy duty, robust and provides a long life service to the user.

### DOUBLE BOLT CLAMP (CAST-ON-SADDLES)

Product Code	Size ins	Size mm	Material
DBC29	1/2	22mm-29mm	Malleable Iron
DBC34	3/4	28mm-34mm	Malleable Iron
DBC40	1	32mm-40mm	Malleable Iron
DBC49	1 1/4	39mm-49mm	Malleable Iron
DBC60	1 1/2	48mm-60mm	Malleable Iron
DBC72	2	56mm-72mm	Malleable Iron
DBC76	2	60mm-76mm	Malleable Iron
DBC94	2 1/2	77mm-94mm	Malleable Iron
DBC400	3	89mm-101mm	Malleable Iron
DBC115	3	94mm-115mm	Malleable Iron
DBC525	3 1/2	113mm-127mm	Malleable Iron
DBC145	3 1/2	115mm-145mm	Malleable Iron
DBC550	4	127mm-140mm	Malleable Iron
DBC600	4	135mm-155mm	Malleable Iron
DBC769	6	175mm-195mm	Malleable Iron

### DOUBLE BOLT CLAW CLAMP (LOOSE SADDLES & SAFETY CLAW)

Product Code	Size ins	Size mm	Material
SK29	1/2	22mm-29mm	Malleable Iron
SK34	3/4	28mm-32mm	Malleable Iron
SK39	1	35mm-42mm	Malleable Iron
SK44	1 7/64	42mm-45mm	Malleable Iron
SK51	1 3/8	45mm-53mm	Malleable Iron
SK60	1 5/8	55mm-60mm	Malleable Iron
SK73	2	60mm-73mm	Malleable Iron
SK75	3	86mm-104mm	Malleable Iron

# HOSE CLAMPS



## TECHNICAL SPECIFICATION

- Hose clamps made of malleable iron zinc plated and yellow passivated (free of chrome VI)
- Robust, easy and secure hose assembly for various fittings and applications
- Max. Working Pressure
- PN 25 bar

- US-Version Hose Clamps, two parts with safety claws

### Materials

- Clamps: Malleable iron zinc-plated and yellow passivated (free of chrome VI)
- Screws: Steel zinc-plated

Product Code	Hose-o.D./ Range	L	B	Screw size	Screws	Box	Weight
USUC21-27	21-27	45	55	M 8x35	2	10	171
USUC30-35	30-35	43	65	M 8x45	2	10	176
USUC30-33	30-33	64	70	M 10x50	2	1	405
USUC33-38	33-38	70	71	M 10x50	2	1	413
USUC38-43	38-43	68	78	M 10x60	2	1	433
USUC34-45	34-45	70	85	M 10x50	2	1	500
USUC63-70	63-70	100	120	M 12x80	4	1	1503

# DIN 2817 CLAMPS IN ALUMINIUM



## FEATURES & BENEFITS

- Reusable
- Robust
- ASL Branded
- 'Bolt-shelf' for one handed spanner tightening
- Larger sizes available upon request

## APPLICATIONS

- High Pressure Hose Assemblies
- Steam
- Compressed Air

## TECHNICAL SPECIFICATION

- Sizes: 3/4" to 4" Inner Diameter
- Aluminium

- Interlocking – Extended Finger engages behind annular security collar
- Ribbed

## SUMMARY

**DIN 2817 Style Hose Clamps** as part of our DIN couplings range of fittings. These Aluminium/Stainless Steel clamps are reusable and incorporate a lip, which is designed to engage behind an annular security collar on the hose stem to positively prevent hose 'blow off'. DIN 2817 Style Hose Clamps are a streamline design and the bolts sit in a recess, which leaves no projections to snag or injure an operator.

Product Code	Nominal Size (mm)		Bolt Type	Max Working Pressure	
	Min	Max		Bar	PSI
ASLRS19X6-AL	30	33	M6 x 20	16	230
ASLRS25X6-AL	36	39	M6 x 20	16	230
ASLRS25X8-AL	40	43	M6 x 20	16	230
ASLRS32X6-AL	43	46	M6 x 20	16	230
ASLRS38X6.5-AL	50	52	M6 x 20	16	230
ASLRS38X8-AL	53	56	M6 x 20	16	230
ASLRS38X10-AL	57	60	M6 x 20	16	230
ASLRS45X7-AL	58	61	M8 x 25	16	230
ASLRS50X8-AL	64	67	M8 x 25	16	230
ASLRS50X10-AL	69	71	M8 x 25	16	230
ASLRS63X8-AL	78	82	M8 x 25	16	230
ASLRS75X8-AL	89	93	M8 x 25	16	230
ASLRS80X10-AL	99	102	M8 x 25	16	230
ASLRS100X8-AL	114	119	M10 x 40	16	230
ASLRS100X10-AL	118	122	M10 x 40	16	230

# TRI CLAMP UNIONS



## FEATURES & BENEFITS

- Popular style for process line equipment
- Easy to install and dismantle
- Superior corrosion resistance
- Long service life
- Low cost
- Leak-tight connections
- Adaptable to other forms of piping

## APPLICATIONS

- Food
- Beverage
- Pharmaceutical
- Chemical

## TECHNICAL SPECIFICATION

- Meets FDA requirements and 3A Sanitary standards
- Chemical compatible for use with corrosive acids and bases
- Available in 304 Stainless Steel
- Sizes from 3/4" to 2"
- Designed to be 'clean in place'

## SUMMARY

Tri-Clamp Unions are a very popular hygienic fitting due to providing a smooth, non-contaminating internal pipework joint. A range of tri-clamp unions and seals are available.

## TRI CLAMPS

Product Code	Size ins	Size mm	Material
TRI-050-C	1/2	13	304 Stainless Steel
TRI-075-C	3/4	18	304 Stainless Steel
TRI-100-C	1	25	304 Stainless Steel
TRI-150-C	1 1/2	38	304 Stainless Steel
TRI-200-C	2	50	304 Stainless Steel
TRI-250-C	2 1/2	63	304 Stainless Steel
TRI-300-C	3	75	304 Stainless Steel
TRI-400-C	4	100	304 Stainless Steel



# NOTES

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.